

Product Name:	ABT-HC-19
Description:	<p>Premier Glass Door Laboratory Refrigerator 19 Cu. Ft. capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Recessed door handle LED interior lights are safety shielded and switch controlled Swivel casters (adds 4" to height) Probe access port (3/8") White laminated vinyl exterior White aluminum liner and stainless steel floor interior HFC-free refrigerant (R290), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 27 1/8" W x 25 1/2" D x 82 5/8" H with casters; 78 5/8" H without casters Cycle defrost 115V, 60 Hz, 5.4 Amps, 1/3 HP BTU/HR 4932 UL/C-UL listed Shipping weight: 295 lbs.</p>