

Product Name:	ABT-HC-CP-33
Description:	<p>Premier Glass Door Chromatography Refrigerator 33 Cu. Ft. capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm; Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Eight adjustable shelves (adjustable in ½" increments) Keyed door lock One GFCI protected duplex electrical outlet Two 2" access ports with spring-loaded, self-closing gasketed metal covers Forced draft air circulation Magnetic door gasket for positive seal and integrated door handles LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (3/4") Advanced hydrocarbon detector White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 41 1/8" W* x 33 1/4" D x 81 3/4" H with casters; 78 1/4" H without casters. *Width w/access ports closed; 49 1/8" width w/access ports open Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 419 lbs. Note: This unit requires two (2) outlets</p>