ABT-HC-RFC7A
Premier Refrigerator & Freezer Combination with Auto Defrost Freezer
7 Cu. Ft. capacity (5.2 Ref./1.3 Freezer)
Two exterior swing doors (glass door refrigerator/solid door freezer), right hinged, not reversible
Microprocessor temperature controller, refrigerator and freezer Digital temperature display, refrigerator and freezer
Audible and visual high and low temperature alarms, refrigerator and freezer
2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer
Remote alarm contacts, refrigerator and freezer
Adjustable operating temperature range: Refrigerator: 1°C – 10°C
Adjustable operating temperature range: Freezer:-15°C – -25°C
Auto defrost cycle every 6 hours, max air temp in empty freezer:
+4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp
in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C.
3 adjustable shelves refrigerator/2 adjustable shelves freezer,
shelves have guard rails to prevent product from being pushed against back wall
Footed bottom shelf refrigerator, and freezer
Back wall evaporator cover
Forced draft circulation
Keyed door locks Magnetic door gasket for positive seal
Integrated door handles
Leveling legs
Stacking kit
Two probe access ports (3/8"); one, refrigerator/one, freezer White powder coated exterior
HFC-free refrigerant (R600a), foam insulation and packaging
Two year parts and labor warranty, plus an additional three year
compressor parts warranty
Exterior dimensions: 23 ³ / ₄ "W x 24 ¹ / ₄ "D x 53 1/8"H
Auto defrost freezer / cycle defrost refrigerator
115V, 60 Hz, 1.3 Amps refrigerator, 1 Amps freezer, 1/6 HP refrigerator, 1/8 HP freezer
UL/C-UL listed
Shipping weight: 207 lbs.
*Please note this unit requires 2 outlets.
DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and

ice. Although the heater helps speed up the frost and ice removal, it
can raise the temperatures within the freezer.