Product Name:	ABT-HC-UCFS-0120A-LH
Description:	·
	Freestanding-LEFT HINGED
	1.3 Cu. Ft. Capacity
	One solid swing door, left hinged
	Microprocessor temperature controller
	Digital temperature display
	Audible and visual high and low temperature alarms
	2 probes; 1 in air and 1 in sample bottle Remote alarm contacts
	Adjustable operating temperature range: -15°C – -25°C
	Auto defrost cycle every 6 hours, max air temp in empty freezer:
	+4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp
	in empty freezer: -4.76°C; max sample temp in loaded freezer: -
	9.58°C.
	2 adjustable shelves with guard rail to prevent product from being
	pushed against back wall
	Bottom footed shelf to allow air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Leveling legs
	LED interior light
	Probe access port (3/8")
	Powder coat exterior
	High density urethane foam cabinet and door insulation
	HFC-free refrigerant (R600a), foam insulation and packaging
	Two year parts and labor warranty, plus an additional three year
	compressor parts only warranty
	Pyxis®, Omnicell® and AcuDose RX® compatible
	Exterior dimensions: 23 3/4"W x 24"D x 20 3/8"H
	Note: This unit must have 4" clearance on sides and back for
	adequate ventilation
	Energy Star Certified for Laboratory Refrigerators and Freezers
	Auto defrost
	115V, 60 Hz, 1 Amp,1/8 HP
	Energy Consumption 1.4 kWh/day
	ADA compliant
	UL/C-UL listed
	Shipping weight: 106 lbs.
	DISCLAIMER: Auto defrost freezers incorporate an electric heater
	installed on the evaporator that assist in the removal of the frost and
	ice. Although the heater helps speed up the frost and ice removal, it
	can raise the temperatures within the freezer.