accuc@ld

AFZ5PVBIADADL2B



31.75" x 23.38" x 25" (H x W x D)

Performance series Pharma-Vac 4 cu.ft. ADA height purpose-built vaccine storage freezer designed for recessed or freestanding installation, with factory-installed NIST calibrated temperature logger (DDL)

Highlights:

NIST calibrated DDL included for accurate temperature logging

Sized just under 32" high to fit under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

Product Features:

Performance Series freezer	Purpose-built all-freezer for vaccine storage in medical, pharmaceutical, and life science applications
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
ADA Compliant	Just under 32" tall designed to fit under ADA compliant counters
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our website
Commercial design	Meets UL-471 commercial standards
Adjustable temperature	Intuitive controls let you adjust the interior temperature between -30°C to -10°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
ACCUCOLD DIVISION, FELIX STORCH, IN	IC. ISO 9001:2015 Certified

accuc@ld

AFZ5PVBIADADL2B Specifications:

Overview	
Height of Cabinet	31.75" (81 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	25.0" (64 cm)
Depth with Handle	26.75" (68 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	3.88 cu.ft. (110 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	125.0 lbs. (57 kg)
Shipping Weight	165.0 lbs. (75 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101104065
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	22.5" (57 cm)
1 . 1 140.10	
Interior Width	18.0" (46 cm)
Interior Width Interior Depth	18.0" (46 cm) 18.0" (46 cm)
Interior Depth	18.0" (46 cm)
Interior Depth Shelf Type	18.0" (46 cm) Wire
Interior Depth Shelf Type Shelf Qty	18.0" (46 cm) Wire
Interior Depth Shelf Type Shelf Qty Adjustable Shelves	18.0" (46 cm) Wire 4 Yes
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type	18.0" (46 cm) Wire 4 Yes Digital
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light	18.0" (46 cm) Wire 4 Yes Digital Yes
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type	18.0" (46 cm) Wire 4 Yes Digital Yes R290a
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount	18.0" (46 cm) Wire 4 Yes Digital Yes R290a 1.73 oz.
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI	18.0" (46 cm) Wire 4 Yes Digital Yes R290a 1.73 oz. 280.0
Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	18.0" (46 cm) Wire 4 Yes Digital Yes R290a 1.73 oz. 280.0 130.0

