
# **ARS12PV-FS24LSTACKMED2**



83.5" x 23.38" x 24.38" (H x W x D)

Stacked combination of ARS12PV all-refrigerator with antimicrobial, silver-ion handle and hospital grade cord with 'green dot' plug and FS24LMED2 compact manual defrost all-freezer for vaccine storage

#### **Highlights:**

Independent refrigerator and freezer storage in one slimfitting footprint for space-challenged facilities

Intelligent microprocessor digital temperature controller for optimum temperature management

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

#### **Product Features:**

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint
ARS12PV all-refrigerator	12 cu.ft. automatic defrost all-refrigerator with digital controls, antimicrobial handle, wire shelving, and keyed lock for added security
FS24LMED2 all-freezer	Compact manual defrost all-freezer with digital thermostat and wire shelving
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation (refrigerator)	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -20° to -15°C (freezer)
Antimicrobial silver ion-coated handle (refrigerator)	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs

## accuc@ld

### ARS12PV-FS24LSTACKMED2 Specifications:

Overview			
Height of Cabinet	83.5" (212 cm)		
Width	23.38" (59 cm)		
Width with Door Open	23.88" (61 cm)		
Depth	24.38" (62 cm)		
Depth with Handle	26.13" (66 cm)		
Depth with door at 90°	46.5" (118 cm)		
Capacity	13.4 cu.ft. (379 L)		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	2.8		
Voltage/Frequency	115 V AC/60 Hz		
Weight	215.0 lbs. (98 kg)		
Shipping Weight	280.0 lbs. (127 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101077673		
Refrigerator-Freezer			
Door Swing	RHD		
D "11			

Compressor Warranty	5 Years
UPC	761101077673
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Interior Light	Yes
Refrigerator - Interior Height	53.0" (135 cm)
Refrigerator - Interior Width	20.0" (51 cm)
Refrigerator - Interior Depth	17.0" (43 cm)
Refrigerator - Capacity	12.0 cu.ft
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	7
Refrigerator - Temperature Range	2 to 8°C
Refrigerator - Refrigerant Type	R600a
Refrigerator - Refrigerant Amount	2.11 oz.
Freezer - Interior Height	14.38" (37 cm)

Freezer - Interior Width	13.5" (34 cm)
Freezer - Interior Depth	13.25" (34 cm)
Freezer - Capacity	1.4 cu.ft
Freezer - Shelf Type	Wire
Freezer - Shelf Qty	1
Thermostat Type	Digital
Fan Type	Interior
Freezer - Temperature Range	-20° to -15°C
Freezer - Refrigerant Type	R600a
Freezer - Refrigerant Amount	0.8 oz.

