accucold

FFAR10PLUS2



54.88" x 23.63" x 23" (H x W x D)

10.1 cu.ft. auto defrost all-refrigerator with lock, NIST calibrated thermometer, digital thermostat, and internal fan

Highlights:

Over 10 cu.ft. of storage in a slim 24" footprint

NIST calibrated thermometer displays the current and high/low temperature to the nearest tenth of a degree


Internal fan-forced cooling for more temperature stability

Product Features:

| Large capacity | 10.1 cu.ft. capacity in a 24" footprint | |
|-------------------------------------|---|--|
| Automatic defrost | Reduced maintenance with auto defrost system | |
| NIST calibrated temperature display | Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button | |
| Buffered temperature probe | Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature | |
| Digital thermostat | Electronic controls ensure easy and intuitive temperature management | |
| Internal fan | Fan-forced cooling ensures the unit is evenly cooled from top to bottom | |
| Factory installed lock | Top-mounted for convenient security (NOTE: lock can alternatively be installed on the unit's side. Specify upon ordering) | |
| Adjustable shelves | Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup | |
| Interior light | Turn the light on and off with a convenient rocker switch | |

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com



accuceld

FFAR10PLUS2 Specifications:

| Height of Cabinet | 56.0" (142 cm) | |
|---|---------------------|--|
| Height to Hinge Cap | 54.88" (139 cm) | |
| Width | 23.63" (60 cm) | |
| Depth | 23.0" (58 cm) | |
| Depth with Handle | 24.75" (63 cm) | |
| Depth with door at 90° | 45.38" (115 cm) | |
| Capacity | 10.1 cu.ft. (286 L) | |
| Defrost Type | Automatic | |
| Door | White | |
| Cabinet | White | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Other Energy Info | 120 Volts / 60 Hz. | |
| Amps | 1.5 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 140.0 lbs. (64 kg) | |
| Shipping Weight | 157.0 lbs. (71 kg) | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| UPC | 761101057705 | |
| Refrigerator Features | | |
| Door Swing | RHD | |
| Reversible | Factory Reversible | |
| Shelf Type | Wire | |
| Shelf Qty | 4 | |
| Adjustable Shelves | Yes | |
| Thermostat Type | Digital | |
| Fan Type | Interior | |
| Refrigerant Type | R134a | |
| | 3.0oz. | |
| Refrigerant Amount | | |
| Refrigerant Amount High Side PSI | 290.0 | |
| | 290.0 70.0 | |
| High Side PSI | | |
| High Side PSI Low Side PSI | 70.0 | |
| High Side PSI Low Side PSI Level Legs Qty | 70.0 | |
| High Side PSI Low Side PSI Level Legs Qty Interior Light | 70.0 2 Yes | |

| Interior Width | 21.0" (53 cm) |
|---------------------------|----------------|
| Interior Depth | 17.75" (45 cm) |
| Compressor Step Height | 6.0" (15 cm) |
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 5.5" (14 cm) |



