

FS30L7NZ



24.63" x 18.5" x 17.75" (H x W x D)

Commercially approved Nutrition Center series compact all-freezer in white with front lock and NIST calibrated digital temperature display

Highlights:

Commercially listed to NSF-7 standards

Digital temperature display and audible alarm allows easier temperature monitoring as recommended by JCAHO

Thermometer is NIST calibrated in our ISO/IEC 17025:2017 laboratory

Product Features:

Commercially approved	ETL-S listed to NSF-7 commercial standards
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Compact dimensions	Sized for easy use on top of counters
Versatile display	Temperature display can be switched from Celsius to Fahrenheit at the touch of a button
Manual defrost	Static cooling system for improved temperature stability
Adjustable thermostat	Dial thermostat located inside the unit
Factory installed lock	Keyed lock for a secure interior
Reversible door	User-reversible door swing allows for more flexibility in placing the unit

FS30L7NZ Specifications:

Overview	
Height of Cabinet	27.0" (69 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	43.0 lbs. (20 kg)
Shipping Weight	63.5 lbs. (29 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101061269
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

