

VT65MLBIMED



33.5" x 23.63" x 23.5" (H x W x D)

Built-in undercounter freezer capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

Highlights:

Flexible design allows built-in or freestanding use in 24" wide spaces

Factory installed lock provides security you can count on

High temperature alarm includes external temperature readout

Product Features:

Slim undercounter dimensions	Less than 24" wide to fit tight spaces
Built-in capable	Make the best use of space by installing your appliance under the counter
Factory installed lock	Keyed lock for secure interior
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
-25°C capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Adjustable thermostat	Manage the temperature with ease and accuracy
Pull-out drawers	Clear baskets for convenient and separated storage

VT65MLBIMED Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Weight	105.0 lbs. (48 kg)
Shipping Weight	118.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101034133
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

