

VT65MLMEDADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant 24" wide all-freezer for freestanding use capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

Highlights:

- 32" height for use in settings following ADA guidelines
- Factory installed lock provides security you can count on
- 25° C operation for safe storage of temperature sensitive materials

Product Features:

ADA compliant	32" height for use in settings following ADA guidelines
Factory installed lock	Keyed lock for secure interior
-25°C capable	Low temperature capability ideal for certain sensitive items
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Manual defrost	Efficient performance with reliable temperature stability
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Pull-out drawers	Clear baskets for convenient and separated storage
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management

VT65MLMEDADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	118.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101038391
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

