

Product Name:	CRT-ABT-HC-S23S
Description:	<p>Upright Controlled Room Temperature Cabinet, Solid Door  23 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor temperature controller  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  2 probes; 1 in air and 1 in sample bottle  Four adjustable shelves (adjustable in ½” increments)  Vaccine storage power cord warning label  Forced draft air circulation  LED interior lights are safety shielded and switch controlled  Swivel Casters (3”)  Probe access port (¾”)  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  One year parts and labor warranty, plus an additional four year compressor parts warranty  Exterior dimensions: 26 7/8” W x 34 3/4” D x 81 3/4” H with casters; 78 1/4” H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  UL/C-UL listed  Shipping weight: 250 lbs.</p>