

Product Name:	CRT-ABT-HC-S36S
Description:	<p>Upright Controlled Room Temperature Cabinet, Solid Door  36 Cu. Ft. capacity  Two swing solid doors, self-closing, right hinged, not reversible  Microprocessor temperature controller  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  Keyed door locks  Magnetic door gasket for positive seal  2 probes; 1 in air and 1 in sample bottle  Eight adjustable shelves  Vaccine storage power cord warning label  Forced draft air circulation  Heavy duty door handles  LED interior lights are safety shielded and switch controlled  Swivel Casters (3")  Probe access port (<math>\frac{3}{8}</math>")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  One year parts and labor warranty, plus an additional four year compressor parts warranty  Exterior dimensions: 39 <math>\frac{5}{8}</math>" W x 34 <math>\frac{3}{4}</math>" D x 81 <math>\frac{3}{4}</math>" H with casters; 78 <math>\frac{1}{4}</math>" H without casters  Cycle defrost  115V, 60 Hz, 4.5 Amps, 1/4 HP  ETL listed  Shipping weight: 360 lbs.</p>