

Product Name:	CRT-ABT-HC-UCFS-0204G
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Freestanding  2.5 Cu. Ft. Capacity  One glass swing door, right hinged, not reversible  Microprocessor temperature controller  Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  2 probes; 1 in air and 1 in sample bottle  Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall  Back wall evaporator cover  Vaccine storage power cord warning label  Forced draft circulation  Keyed door lock  Magnetic door gasket for positive seal  Leveling legs  LED interior light  Probe access port (3/8")  Powder coat exterior  High density urethane foam cabinet and door insulation  HFC-free refrigerant (R600a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts only warranty  Pyxis<sup>®</sup>, Omnicell<sup>®</sup> and AcuDose RX<sup>®</sup> compatible  Exterior dimensions: 17 3/4"W x 19 1/2"D x 28 7/8"H  <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i>  Cycle defrost  115V, 60 Hz, .90 Amps, 1/8 HP  ENERGY STAR CERTIFIED  ADA compliant  Shipping weight: 97 lbs.</p>