Product Name:	PH-ABT-HC-47G
Description:	, , ,
	47 Cu. Ft. capacity
	Two sliding glass doors, self-closing (energy efficient, double pane
	vacuum insulated)
	Microprocessor Temperature Controller
	Adjustable operating temperature range: $36^{\circ}F - 46^{\circ}F (2^{\circ}C - 8^{\circ}C)$
	Temperature monitor device (TMD) complies with the current CDC
	guidelines, with 3 years certification of calibration, "buffered" probe
	in the product simulated solution, min/max memory. F/C switchable,
	field installable, and visual & audible temp alarm
	Standard Digital Temperature Display and Alarm Module with
	battery back-up to support temperature monitoring and alarms
	Sample simulated digital temperature display; .1° Resolution
	Adjustable temperature display in Celsius or Fahrenheit
	Audible and visual high/low temperature alarms
	2 probes; 1 in air and 1 in sample bottle
	Sensor error alarm
	Power failure alarm
	Resettable 1-point Min/Max History
	Remote alarm contacts
	Alarm validation (audible, visual, and remote alarm)
	Alarm mute with ring back
	Vaccine storage power cord warning label
	12 total shelves, 8 adjustable plus 4 additional
	Forced draft air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Integrated door handles
	LED interior lights are safety shielded and switch controlled Swivel Casters (3 1/2")
	Probe access port (³ / ₈ ")
	Powder coated steel white exterior and interior
	Hydrocarbon, natural refrigerant (R290)
	Pharmacy refrigerator/freezer toolkit and temperature logs
	Two year parts and labor warranty, plus an additional three year
	compressor parts warranty
	Exterior dimensions: 54 $\frac{1}{8}$ " W x 33 $\frac{1}{4}$ " D x 81 $\frac{3}{4}$ " H with casters; 78
	$\frac{1}{4}$ " H without casters
	Cycle defrost
	115V, 60 Hz, 4.5 Amps, 1/4 HP
	ETL listed
	Shipping weight: 508 lbs.